






DESCRIPTION			
Total thickness	EN 428	mm	6.00
Wearlayer thickness	EN 429	mm	2
Weight	EN 430	g/m ²	9240
Size	EN 427	mm	635 X 635
CLASSIFICATION			
Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
Fire rating	EN 13 501-1	class	B _f -s1
Electrical resistance	EN 1081	Ω	$5 \times 10^4 \leq Rt \leq 10^6$
	IEC 61.340-4-1		$\leq 10^8$
	ANSI/ESD 7.1		$2.5 \times 10^4 \leq Rt \leq 10^6$
Static electrical propensity	EN 1815	kV	< 2
	IEC 61340-4-5	V	≤ 100 *
Protection against electrostatic discharges	ESD S20.20	-	OK
	IEC 61340-5-1	-	OK
Slip resistance wet : ramp test with oil	DIN 51130	class	R9
PERFORMANCES			
Wear resistance	EN 660.2	mm ³	≤ 4
Wear group	EN 649	group	P
Type binder content	ISO 10582	type	I
Dimensional stability	EN 434	%	≤ 0.25
Shore hardness	EN ISO 868	Hd	≥ 90
Castor chair test (type W)	EN 425	-	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	Evercare™
Chemical product resistance	EN 423	class	OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
Certification	-	-	Floorscore®
CE MARKING			
	EN 14041	-	  
		-	

* Measured with ESD shoes (type ABEBA and Uvex)